


UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Double-level terminal block, nom. voltage: 500 V, nominal current: 24 A, connection method: Screw connection, 1st and 2nd level, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Your advantages

- Large-surface labeling option

Commercial data

Item number	2771010
Packing unit	50 pc
Minimum order quantity	1 pc
Sales key	BE01
Product key	BE1214
GTIN	4017918068165
Weight per piece (including packing)	14.87 g
Weight per piece (excluding packing)	13.97 g
Customs tariff number	85369010
Country of origin	CN

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Technical data

Product properties

Product type	Multi-level terminal block
Product family	UK
Number of connections	4
Number of rows	2
Potentials	2

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	0.77 W

Connection data

Number of connections per level	2
Nominal cross section	2.5 mm ²
Rated cross section AWG	12

1st and 2nd level

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.5 ... 0.6 Nm
Stripping length	8 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross-section rigid	0.2 mm ² ... 4 mm ²
Cross section AWG	24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section, flexible [AWG]	24 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 2.5 mm ²
Flexible conductor cross-section (ferrule with plastic sleeve)	0.25 mm ² ... 1.5 mm ²
Cross-section with insertion bridge, rigid	2.5 mm ²
Cross-section with insertion bridge, flexible	2.5 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 1 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 1.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 1.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 1 mm ²
Nominal current	24 A
Maximum load current	32 A (in case of a 4 mm ² conductor cross-section, the maximum load current must not be exceeded by the total current of all

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

	connected conductors.)
Nominal voltage	500 V
Nominal cross section	2.5 mm ²

Dimensions

Width	5.2 mm
End cover width	2.5 mm
Height	67 mm
Depth on NS 32	67 mm
Depth on NS 35/7,5	62 mm
Depth on NS 35/15	69.5 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	7.3 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 2.5 mm ²	0.3 kA
Short-time withstand current 4 mm ²	0.48 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross-section/weight	0.2 mm ² / 0.2 kg
	2.5 mm ² / 0.7 kg
	4 mm ² / 0.9 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

UKKB 3 - Double-level terminal block




2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Drawings

Circuit diagram



UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/2771010>



CSA
Approval ID: 13631



cUL Recognized
Approval ID: FILE E 60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	600 V	20 A	28 - 12	-



IECEE CB Scheme
Approval ID: NL-65063

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	500 V	24 A	-	- 2.5



EAC
Approval ID: KZ7500651131219505



cULus Recognized
Approval ID: E60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	300 V	20 A	28 - 12	-
Multi-conductor connection	300 V	20 A	28 - 16	-
C				
	300 V	20 A	28 - 12	-
Multi-conductor connection	300 V	20 A	28 - 16	-
D				
	600 V	5 A	28 - 12	-
Multi-conductor connection	600 V	5 A	28 - 16	-



KEMA-KEUR
Approval ID: 71-113433

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

	500 V	-	-	- 2.5
--	-------	---	---	-------

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Classifications

ECLASS

ECLASS-13.0	27250102
ECLASS-15.0	27250102

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	ec560035-4806-4306-b5d6-27d6ead943ba
EF3.0 Climate Change	
CO2e kg	0.141 kg CO2e

UKKB 3 - Double-level terminal block



2771010

<https://www.phoenixcontact.com/ca/products/2771010>

Accessories



Note: Applying some accessories below might limit this product.

FBRNI 20-5 N - Fixed bridge

3000609

<https://www.phoenixcontact.com/ca/products/3000609>



Fixed bridge, number of positions: 20, color: silver-colored

FBRNI 2-5 N - Fixed bridge

3000175

<https://www.phoenixcontact.com/ca/products/3000175>



Fixed bridge, pitch: 5 mm, number of positions: 2, color: silver-colored



Max. current carrying capacity: 28 A

UKKB 3 - Double-level terminal block




2771010

<https://www.phoenixcontact.com/ca/products/2771010>

FBRNI 3-5 N - Fixed bridge

3000162

<https://www.phoenixcontact.com/ca/products/3000162>




Fixed bridge, pitch: 5 mm, number of positions: 3, color: silver-colored

 Max. current carrying capacity: 28 A

FBRNI 4-5 N - Fixed bridge

3000159

<https://www.phoenixcontact.com/ca/products/3000159>



Fixed bridge, pitch: 5 mm, number of positions: 4, color: silver-colored

 Max. current carrying capacity: 28 A

UKKB 3 - Double-level terminal block

2771010


<https://www.phoenixcontact.com/ca/products/2771010>



FBRNI 10-5 N - Fixed bridge

2770639

<https://www.phoenixcontact.com/ca/products/2770639>



Fixed bridge, pitch: 5.2 mm, number of positions: 10, color: silver-colored

 Max. current carrying capacity: 28 A

EBL 3- 5 - Insertion bridge

2303158

<https://www.phoenixcontact.com/ca/products/2303158>

Insertion bridge, pitch: 5.2 mm, number of positions: 3, color: gray



UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



EBL 2- 5 - Insertion bridge

2303145

<https://www.phoenixcontact.com/ca/products/2303145>

Insertion bridge, pitch: 5.2 mm, number of positions: 2, color: gray



EBL 10- 5 - Insertion bridge

2303132

<https://www.phoenixcontact.com/ca/products/2303132>

Insertion bridge, pitch: 5.2 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 22 A

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



USBR 2-7 - Bridge bar

2303239

<https://www.phoenixcontact.com/ca/products/2303239>



Bridge bar, pitch: 7 mm, number of positions: 2, color: silver-colored

USBRJ 2-7 - Bridge bar

2305538

<https://www.phoenixcontact.com/ca/products/2305538>



Bridge bar, number of positions: 2, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



SBRN 2-7 - Bridge bar

1413230

<https://www.phoenixcontact.com/ca/products/1413230>

Bridge bar, pitch: 7 mm, number of positions: 2, color: silver-colored



DP-UKKB 3/ 5 - Spacer plate

2770804

<https://www.phoenixcontact.com/ca/products/2770804>

Spacer plate, to compensate for level offsets, depth: 25 mm, width: 2.5 mm, height: 67 mm, color: gray



UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



DG-UKKB 3/ 5 - Spacer plate

2770859

<https://www.phoenixcontact.com/ca/products/2770859>



Spacer plate, to compensate for level offsets, width: 2.5 mm, height: 67 mm, color: gray

D-UKKB 3/5 - End cover

2771023

<https://www.phoenixcontact.com/ca/products/2771023>



End cover, depth: 52 mm, width: 2.5 mm, height: 67.2 mm, color: gray

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



KSS 5 - Short-circuit connector

2303543

<https://www.phoenixcontact.com/ca/products/2303543>



Short-circuit connector, pitch: 5 mm, number of positions: 2, color: black

PS-UKK 3 - Test plug

3000638

<https://www.phoenixcontact.com/ca/products/3000638>



Test plug, number of positions: 10, color: red

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



PS-UKK/E - Test plug

3000641

<https://www.phoenixcontact.com/ca/products/3000641>



Test plug, number of positions: 1, color: red

RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/ca/products/0201647>



Reducing plug, number of positions: 1, color: gray

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



TS-KK 3 - Separating plate

2770215

<https://www.phoenixcontact.com/ca/products/2770215>



Separating plate, depth: 16 mm, width: 0.5 mm, height: 14 mm, color: gray

ATP-UKKB 3 - Partition plate

2771065

<https://www.phoenixcontact.com/ca/products/2771065>



Partition plate, depth: 67 mm, width: 2.5 mm, height: 75 mm, color: gray

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



SBS 5:UNBEDRUCKT - Marker card

1007219

<https://www.phoenixcontact.com/ca/products/1007219>



Marker card, Card, white, unmarked, can be labeled with: Marker pen, perforated, mounting type: snap into tall marker groove, snap into flat marker groove, for terminal block width: 5 mm, Number of individual labels: 250

NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/ca/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/ca/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver-colored

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ca/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ca/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ca/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ca/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ca/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ca/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ca/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ca/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ca/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ca/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ca/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ca/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: white

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ca/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ca/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ca/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ca/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ca/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ca/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ca/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



ZB 5 :UNBEDRUCKT - Zack marker strip

1050004

<https://www.phoenixcontact.com/ca/products/1050004>



Zack marker strip, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.1 mm

ZB 5,LGS:FORTL.ZAHLEN - Zack marker strip

1050017

<https://www.phoenixcontact.com/ca/products/1050017>



Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.15 mm

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>

ZB 5,QR:FORTL.ZAHLEN - Zack marker strip

1050020

<https://www.phoenixcontact.com/ca/products/1050020>



Zack marker strip, Strip, white, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.15 mm

ZB 5,LGS:GLEICHE ZAHLEN - Zack marker strip

1050033

<https://www.phoenixcontact.com/ca/products/1050033>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.15 mm

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



ZB 5,LGS:L1-N,PE - Zack marker strip

1050415

<https://www.phoenixcontact.com/ca/products/1050415>



Zack marker strip, Strip, white, labeled, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 5.15 mm

UC-TM 5 - Marker for terminal blocks

0818108

<https://www.phoenixcontact.com/ca/products/0818108>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 96, text field height: 10.5 mm, text field width: 4.6 mm

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



UCT-TM 5 - Marker for terminal blocks

0828734

<https://www.phoenixcontact.com/ca/products/0828734>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 72, text field height: 10.5 mm, text field width: 4.6 mm

GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/ca/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



GBS 5-25X5 - Group marker label for terminal marking

0829126

<https://www.phoenixcontact.com/ca/products/0829126>



Group marking label, can be snapped into terminal center for screw, spring-cage, push-in, and fast connection terminal blocks, can be labeled with a 24 x 4 mm label or manually using B-STIFT, in the foot part with ZB 5

CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ca/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ca/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ca/products/0800886>



End clamp, width: 9.5 mm, color: gray

UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



PSBJ 3/13/4 - Test plug strip

0201304

<https://www.phoenixcontact.com/ca/products/0201304>



Test plug strip, number of positions: 1, color: silver-colored

PSB 3/10/4 - Test plug strip

0601292

<https://www.phoenixcontact.com/ca/products/0601292>



Test plug strip, number of positions: 1, color: silver-colored

UKKB 3 - Double-level terminal block



2771010


<https://www.phoenixcontact.com/ca/products/2771010>

E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ca/products/1201442>

End bracket, material: PA, mounting type: NS 35/7,5, NS 35/15, color: gray



E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ca/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



UKKB 3 - Double-level terminal block

2771010

<https://www.phoenixcontact.com/ca/products/2771010>



SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/ca/products/1212587>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

8240 Parkhill Drive

Milton, Ontario L9T 5V7

1-800-890-2820

cdinfo@phoenixcontact.ca