


# UK 10 - Feed-through terminal block



3005015

<https://www.phoenixcontact.com/pc/products/3005015>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 57 A, number of connections: 2, connection method: Screw connection, cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: NS 32, NS 35/7,5, NS 35/15, color: gray

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3005015       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Product key                          | BE1211        |
| GTIN                                 | 4017918090982 |
| Weight per piece (including packing) | 15.76 g       |
| Weight per piece (excluding packing) | 14.958 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | DE            |

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Product family        | UK                          |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |      |
|-------------------------------------------------|------|
| Rated surge voltage                             | 8 kV |
| Maximum power dissipation for nominal condition | 0 W  |

### Connection data

#### Level 1 above 1 below 1

|                                                                                           |                                             |
|-------------------------------------------------------------------------------------------|---------------------------------------------|
| Connection method                                                                         | Screw connection                            |
| Screw thread                                                                              | M4                                          |
| Tightening torque                                                                         | 1.5 ... 1.8 Nm                              |
| Stripping length                                                                          | 10 mm                                       |
| Internal cylindrical gage                                                                 | A5                                          |
| Connection in acc. with standard                                                          | IEC / EN                                    |
| Conductor cross-section rigid                                                             | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>  |
| Cross section AWG                                                                         | 20 ... 8 (converted acc. to IEC)            |
| Conductor cross-section flexible                                                          | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| Conductor cross-section, flexible [AWG]                                                   | 20 ... 10 (converted acc. to IEC)           |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| Flexible conductor cross-section (ferrule with plastic sleeve)                            | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Cross-section with insertion bridge, rigid                                                | 6 mm <sup>2</sup>                           |
| Cross-section with insertion bridge, flexible                                             | 6 mm <sup>2</sup>                           |
| 2 conductors with same cross section, solid                                               | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| 2 conductors with same cross section, flexible                                            | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Nominal current                                                                           | 57 A                                        |
| Nominal voltage                                                                           | 800 V                                       |
| Connection in acc. with standard                                                          | UL                                          |
| Cross section AWG                                                                         | 26 ... 8 (converted acc. to IEC)            |
| Nominal current                                                                           | 50 A                                        |

# UK 10 - Feed-through terminal block



3005015

<https://www.phoenixcontact.com/pc/products/3005015>

|                                  |                                  |
|----------------------------------|----------------------------------|
| Nominal voltage                  | 600 V                            |
| Connection in acc. with standard | CSA                              |
| Cross section AWG                | 26 ... 8 (converted acc. to IEC) |
| Nominal current                  | 55 A                             |
| Nominal voltage                  | 600 V                            |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 8.2 mm  |
| End cover width    | 1.8 mm  |
| Height             | 42.5 mm |
| Depth on NS 32     | 52 mm   |
| Depth on NS 35/7,5 | 47 mm   |
| Depth on NS 35/15  | 54.5 mm |

## Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group                                        | I               |
| Insulating material                                              | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                 |                                     |
|-------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test               | Increase in temperature $\leq 45$ K |
| Result                                          | Test passed                         |
| Short-time withstand current 6 mm <sup>2</sup>  | 0.72 kA                             |
| Short-time withstand current 10 mm <sup>2</sup> | 1.2 kA                              |
| Result                                          | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

# UK 10 - Feed-through terminal block



3005015

<https://www.phoenixcontact.com/pc/products/3005015>

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint     | 5 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross-section/weight | 0.5 mm <sup>2</sup> / 0.3 kg |
|                                | 6 mm <sup>2</sup> / 1.4 kg   |
|                                | 10 mm <sup>2</sup> / 2 kg    |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |          |
|----------------------------------|----------|
| Connection in acc. with standard | IEC / EN |
|                                  | UL       |
|                                  | CSA      |

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 32     |
|               | NS 35/7,5 |

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



|  |          |
|--|----------|
|  | NS 35/15 |
|--|----------|

# UK 10 - Feed-through terminal block



3005015

<https://www.phoenixcontact.com/pc/products/3005015>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3005015>

|  <b>CSA</b><br>Approval ID: 13631 |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine                                                                                                              |                       |                       |                   |                             |
|                                                                                                                    | 600 V                 | 55 A                  | 26 - 8            | -                           |

|  <b>EAC</b><br>Approval ID: KZ7500651131219505 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                             |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B                                                                                                                                |                       |                       |                   |                             |
|                                                                                                                                  | 600 V                 | 50 A                  | 26 - 8            | -                           |
| C                                                                                                                                |                       |                       |                   |                             |
|                                                                                                                                  | 600 V                 | 50 A                  | 26 - 8            | -                           |

|  <b>ClassNK</b><br>Approval ID: 09 ME 142 |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>DNV</b><br>Approval ID: TAE00001CT |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|---------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
| ECLASS-15.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |
| EF3.0 Climate Change                    |                                          |
| CO2e kg                                 | 0.062 kg CO2e                            |

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## Accessories



Note: Applying some accessories below might limit this product.

### IS-K 10 - Bridge bar isolator

1303337

<https://www.phoenixcontact.com/pc/products/1303337>



Bridge bar isolator, color: gray

---

### ISSBI 10- 8 - Bridge

0301534

<https://www.phoenixcontact.com/pc/products/0301534>



Bridge, pitch: 8 mm, number of positions: 10, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## FBI 2- 8 - Fixed bridge

0200020

<https://www.phoenixcontact.com/pc/products/0200020>

Fixed bridge, pitch: 8 mm, number of positions: 2, color: silver-colored



---

## FBI 4- 8 - Fixed bridge

0200046

<https://www.phoenixcontact.com/pc/products/0200046>

Fixed bridge, pitch: 8 mm, number of positions: 4, color: silver-colored



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## FBI 10- 8 - Fixed bridge

0203263

<https://www.phoenixcontact.com/pc/products/0203263>

Fixed bridge, pitch: 8 mm, number of positions: 10, color: silver-colored



---

## FBI 3- 8 - Fixed bridge

0200059

<https://www.phoenixcontact.com/pc/products/0200059>

Fixed bridge, pitch: 8 mm, number of positions: 3, color: silver-colored



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## EB 2- 8 - Insertion bridge

0202154

<https://www.phoenixcontact.com/pc/products/0202154>




Insertion bridge, pitch: 8 mm, number of positions: 2, color: gray

---

## EB 3- 8 - Insertion bridge

0202141

<https://www.phoenixcontact.com/pc/products/0202141>




Insertion bridge, pitch: 8 mm, number of positions: 3, color: gray

---

## EB 10- 8 - Insertion bridge

0202138

<https://www.phoenixcontact.com/pc/products/0202138>



Insertion bridge, pitch: 8 mm, number of positions: 10, color: gray

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## SBJ 2- 8/13 - Bridge bar

0303286

<https://www.phoenixcontact.com/pc/products/0303286>

Bridge bar, number of positions: 2, color: silver-colored



---

## SB 2- 8/13 - Bridge bar

0202235

<https://www.phoenixcontact.com/pc/products/0202235>

Bridge bar, pitch: 13 mm, number of positions: 2, color: silver-colored



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## EB 4- 8 - Insertion bridge

0202142

<https://www.phoenixcontact.com/pc/products/0202142>

Insertion bridge, pitch: 8 mm, number of positions: 4, color: gray



 Max. current carrying capacity: 41 A

---

## WS 5- 8 - Warning label

1004416

<https://www.phoenixcontact.com/pc/products/1004416>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 8 mm



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## WS 4- 8 - Warning label

1004212

<https://www.phoenixcontact.com/pc/products/1004212>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 8 mm



---

## WS 3- 8 - Warning label

1004128

<https://www.phoenixcontact.com/pc/products/1004128>

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 8 mm



## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## KSS 8 - Short-circuit connector

0311540

<https://www.phoenixcontact.com/pc/products/0311540>

Short-circuit connector, pitch: 8 mm, number of positions: 2, color: black



---

## STL 35/10 - Step bracket

0204084

<https://www.phoenixcontact.com/pc/products/0204084>

Step bracket, number of positions: 2, color: silver-colored



## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## STL 16/10 - Step bracket

0204518

<https://www.phoenixcontact.com/pc/products/0204518>

Step bracket, number of positions: 2, color: silver-colored



---

## TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/pc/products/1302215>

Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray



## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



### ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/pc/products/3003224>

Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray



---

### D-UK 4/10 - End cover

3003020

<https://www.phoenixcontact.com/pc/products/3003020>

End cover, depth: 35.9 mm, width: 1.8 mm, height: 42.5 mm, color: gray



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## D-UK 4/10 BU - End cover

3003101

<https://www.phoenixcontact.com/pc/products/3003101>

End cover, depth: 47 mm, width: 1.8 mm, height: 42.5 mm, color: blue



---

## NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/pc/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/pc/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver-colored

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/pc/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/pc/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

## UK 10 - Feed-through terminal block

3005015


<https://www.phoenixcontact.com/pc/products/3005015>



### ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/pc/products/1052002>




Zack marker strip, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

---

### ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/pc/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 10.5 mm

## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/pc/products/0818072>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

---

## UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/pc/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/pc/products/0828740>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

---

## UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/pc/products/0829616>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

# UK 10 - Feed-through terminal block


3005015

<https://www.phoenixcontact.com/pc/products/3005015>

## ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/pc/products/1052015>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

---

## ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/pc/products/1052028>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

# UK 10 - Feed-through terminal block

3005015


<https://www.phoenixcontact.com/pc/products/3005015>



## ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/pc/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

---

## CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/pc/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/pc/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

## E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/pc/products/0800886>



End clamp, width: 9.5 mm, color: gray

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>




## E/UK - End bracket

1201442

<https://www.phoenixcontact.com/pc/products/1201442>

End bracket, material: PA, mounting type: NS 35/7,5, NS 35/15, color: gray



---

## E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/pc/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## PSBJ 4/15/6 FARBLOS - Test plug strip

0303419

<https://www.phoenixcontact.com/pc/products/0303419>



Test plug strip, number of positions: 1, color: transparent

---

## PSBJ 4/15/6 WH - Test plug strip

0303312

<https://www.phoenixcontact.com/pc/products/0303312>



Test plug strip, number of positions: 1, color: white

## UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



### PSBJ 4/15/6 RD - Test plug strip

0303325

<https://www.phoenixcontact.com/pc/products/0303325>



Test plug strip, number of positions: 1, color: red

---

### PSBJ 4/15/6 BU - Test plug strip

0303354

<https://www.phoenixcontact.com/pc/products/0303354>



Test plug strip, number of positions: 1, color: blue

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## PSBJ 4/15/6 YE - Test plug strip

0303367

<https://www.phoenixcontact.com/pc/products/0303367>



Test plug strip, number of positions: 1, color: yellow

---

## PSBJ 4/15/6 GN - Test plug strip

0303370

<https://www.phoenixcontact.com/pc/products/0303370>



Test plug strip, number of positions: 1, color: green

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## PSBJ 4/15/6 VT - Test plug strip

0303383

<https://www.phoenixcontact.com/pc/products/0303383>



Test plug strip, number of positions: 1, color: violet

---

## PSBJ 4/15/6 GY - Test plug strip

0303396

<https://www.phoenixcontact.com/pc/products/0303396>



Test plug strip, number of positions: 1, color: gray

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## PSBJ 4/15/6 BK - Test plug strip

0303406

<https://www.phoenixcontact.com/pc/products/0303406>



Test plug strip, number of positions: 1, color: black

---

## PSB 4/7/6 - Test plug strip

0303299

<https://www.phoenixcontact.com/pc/products/0303299>



Test plug strip, number of positions: 1, color: silver-colored

# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## EA 5-WS - Cover

1024085

<https://www.phoenixcontact.com/pc/products/1024085>

Single covers, for covering one terminal block, with black symbol (lightning flash)  
snap fit, color: transparent/yellow



---

## EA 5 - Cover

1024014

<https://www.phoenixcontact.com/pc/products/1024014>

Cover, material: ABS, color: transparent



# UK 10 - Feed-through terminal block

3005015

<https://www.phoenixcontact.com/pc/products/3005015>



## SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/pc/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

---

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)