

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 125 A, number of connections: 2, connection method: Screw connection, cross section: 0.75 mm² - 50 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Your advantages

- The large wiring space enables the connection of solid and stranded conductors without ferrules, even above the nominal cross section
- As well as saving space, the compact design enables user-friendly wiring in a small amount of space
- Optimum screwdriver guidance through closed screw shafts

Commercial data

Item number	3008012
Packing unit	50 pc
Minimum order quantity	50 pc
Product key	BE1211
GTIN	4017918091552
Weight per piece (including packing)	57.97 g
Weight per piece (excluding packing)	55.656 g
Customs tariff number	85369010
Country of origin	DE

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



Technical data

Product properties

Product type	Feed-through terminal block
Product family	UK
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	4.06 W

Connection data

Number of connections per level	2
Nominal cross section	35 mm ²
Rated cross section AWG	2

Level 1 above 1 below 1

Connection method	Screw connection
Screw thread	M6
Tightening torque	3.2 ... 3.7 Nm
Stripping length	16 mm
Internal cylindrical gage	B9
Connection in acc. with standard	IEC 60947-7-1
Conductor cross-section rigid	0.75 mm ² ... 50 mm ²
Cross section AWG	18 ... 2 (converted acc. to IEC)
Conductor cross-section flexible	0.75 mm ² ... 35 mm ²
Conductor cross-section, flexible [AWG]	18 ... 2 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.75 mm ² ... 35 mm ²
Flexible conductor cross-section (ferrule with plastic sleeve)	0.75 mm ² ... 35 mm ²
2 conductors with same cross section, solid	0.75 mm ² ... 16 mm ²
2 conductors with same cross section, flexible	0.75 mm ² ... 10 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.75 mm ² ... 10 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.75 mm ² ... 6 mm ²
Nominal current	125 A
Maximum load current	150 A (with 50 mm ² conductor cross-section)
Nominal voltage	1000 V

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Dimensions

Width	15.1 mm
Height	50 mm
Depth on NS 32	67 mm
Depth on NS 35/7,5	62 mm
Depth on NS 35/15	69.5 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
	Test passed
Short-time withstand current 35 mm ²	4.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2.2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Mechanical tests

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	10 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 (+/- 2) rpm
Revolutions	135
Conductor cross-section/weight	0.75 mm ² / 0.4 kg
	35 mm ² / 6.8 kg
	50 mm ² / 9.5 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2022-06
Spectrum	Long life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s ²) ² /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



Drawings

Circuit diagram



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3008012>

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	600 V	150 A	18 - 1/0	-
C				
	600 V	150 A	18 - 1/0	-
With ATP	1000 V	150 A	18 - 1/0	-

 IECEE CB Scheme Approval ID: NL-26111				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	1000 V	-	-	- 35

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	600 V	150 A	18 - 1/0	-
C				
	600 V	150 A	18 - 1/0	-
F				
	1000 V	150 A	18 - 1/0	-

 KEMA-KEUR Approval ID: 71-119836				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	1000 V	-	-	0.75 - 35

 ClassNK Approval ID: 09 ME 141				
--	--	--	--	--

 DNV Approval ID: TAE00001CT				
---	--	--	--	--

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

 cUL Recognized Approval ID: E192998				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	600 V	150 A	18 - 1/0	-

 EAC Ex Approval ID: KZ 7500525010101950				
---	--	--	--	--

 GL Approval ID: 98876-96 HH				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
EEx e II part certificate	690 V	118.5 A	-	- 35

 UL Recognized Approval ID: E192998				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	600 V	150 A	18 - 1/0	-

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Classifications

ECLASS

ECLASS-13.0	27250101
ECLASS-15.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UK 35 - Feed-through terminal block



3008012

<https://www.phoenixcontact.com/pc/products/3008012>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%
EF3.0 Climate Change	
CO2e kg	0.184 kg CO2e

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



Accessories

i Note: Applying some accessories below might limit this product.

FBI 2-15 - Fixed bridge

0201333

<https://www.phoenixcontact.com/pc/products/0201333>



Fixed bridge, pitch: 15 mm, number of positions: 2, color: silver-colored

i Max. current carrying capacity: 125 A

FBI 3-15 - Fixed bridge

0201278

<https://www.phoenixcontact.com/pc/products/0201278>



Fixed bridge, pitch: 15 mm, number of positions: 3, color: silver-colored

i Max. current carrying capacity: 125 A

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



FBI 5-15 - Fixed bridge

0711302

<https://www.phoenixcontact.com/pc/products/0711302>

Fixed bridge, pitch: 15 mm, number of positions: 5, color: silver-colored



 Max. current carrying capacity: 125 A

EB 2-15 - Insertion bridge

0203166

<https://www.phoenixcontact.com/pc/products/0203166>

Insertion bridge, pitch: 15.25 mm, number of positions: 2, color: gray



 Max. current carrying capacity: 76 A

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>




EB 10-15 - Insertion bridge

0205135

<https://www.phoenixcontact.com/pc/products/0205135>

Insertion bridge, pitch: 15.25 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 76 A

EB 2-15 K/UK 35 - Insertion bridge

0205119

<https://www.phoenixcontact.com/pc/products/0205119>

Insertion bridge, pitch: 15 mm, number of positions: 2, color: gray



 Max. current carrying capacity: 76 A

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>

EB 3-15 K/UK 35 - Insertion bridge

0205106

<https://www.phoenixcontact.com/pc/products/0205106>

Insertion bridge, pitch: 15 mm, number of positions: 3, color: gray



 Max. current carrying capacity: 76 A

EB 10-15 K/UK 35 - Insertion bridge

0205096

<https://www.phoenixcontact.com/pc/products/0205096>

Insertion bridge, pitch: 15 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 76 A

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



SBH 2-15 - Bridge bar

0205232

<https://www.phoenixcontact.com/pc/products/0205232>



Bridge bar, pitch: 15 mm, number of positions: 2, color: silver-colored

 Max. current carrying capacity: 120 A

FBI 2-15 IB - Fixed bridge

3057319

<https://www.phoenixcontact.com/pc/products/3057319>



Fixed bridge, with Allen screws and SW 4 (wrench size), number of positions: 2, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



FBI 3-15 IB - Fixed bridge

3057322

<https://www.phoenixcontact.com/pc/products/3057322>



Fixed bridge, with Allen screws and SW 4 (wrench size), number of positions: 3, color: silver-colored

WS 5-15 - Warning label

1004445

<https://www.phoenixcontact.com/pc/products/1004445>



Warning label, Plate, orange, labeled: Lightning flash and warning in English, mounting type: plug in, for terminal block width: 15 mm, Number of individual labels: 1

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



WS 4-15 - Warning label

1004241

<https://www.phoenixcontact.com/pc/products/1004241>

Warning label, Plate, orange, labeled: Lightning flash and warning in English, mounting type: plug in, for terminal block width: 15 mm, Number of individual labels: 1



STL 35/10 - Step bracket

0204084

<https://www.phoenixcontact.com/pc/products/0204084>

Step bracket, number of positions: 2, color: silver-colored



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



STL 35/ 5 - Step bracket

0204107

<https://www.phoenixcontact.com/pc/products/0204107>

Step bracket, pitch: 5 mm, number of positions: 2, color: silver-colored



STL 35/16 - Step bracket

0204097

<https://www.phoenixcontact.com/pc/products/0204097>

Step bracket, number of positions: 2, color: silver-colored



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/pc/products/1302215>



Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

TP-UK 35 - Separating plate

3008096

<https://www.phoenixcontact.com/pc/products/3008096>



Separating plate, depth: 52 mm, width: 7.5 mm, height: 50 mm, color: gray

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/pc/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/pc/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver-colored

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: white

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, zinc plating, Standard profile, color: silver-colored

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/pc/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/pc/products/1201798>




DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

ZB 15:UNBEDRUCKT - Zack marker strip

0811972

<https://www.phoenixcontact.com/pc/products/0811972>



Zack marker strip, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 15.2 mm, Number of individual labels: 5, text field height: 10.5 mm, text field width: 15.1 mm

UK 35 - Feed-through terminal block

3008012


<https://www.phoenixcontact.com/pc/products/3008012>



ZB 15 CUS - Zack marker strip

0824945

<https://www.phoenixcontact.com/pc/products/0824945>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 15.2 mm, Number of individual labels: 5, text field height: 15.1 mm, text field width: 10.5 mm

ZB 15,LGS:L1-N,PE - Zack marker strip

0811998

<https://www.phoenixcontact.com/pc/products/0811998>



Zack marker strip, Strip, white, labeled, printed horizontally: L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 15.2 mm, Number of individual labels: 5, text field height: 10.5 mm, text field width: 15.1 mm

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/pc/products/0311647>

Test plug, number of positions: 1, color: silver



PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/pc/products/0311566>

Insulating sleeve, number of positions: 1, color: white



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/pc/products/0311579>

Insulating sleeve, number of positions: 1, color: red



PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/pc/products/0311582>

Insulating sleeve, number of positions: 1, color: blue



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/pc/products/0311595>

Insulating sleeve, number of positions: 1, color: yellow



PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/pc/products/0311605>

Insulating sleeve, number of positions: 1, color: green



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/pc/products/0311621>



Insulating sleeve, number of positions: 1, color: gray

PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/pc/products/0311634>



Insulating sleeve, number of positions: 1, color: black

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/pc/products/0311618>

Insulating sleeve, number of positions: 1, color: violet



CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/pc/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/pc/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/pc/products/0800886>



End clamp, width: 9.5 mm, color: gray

UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>




E/UK - End bracket

1201442

<https://www.phoenixcontact.com/pc/products/1201442>

End bracket, material: PA, mounting type: NS 35/7,5, NS 35/15, color: gray



E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/pc/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



PSB 6/5/6 - Test plug strip

0205290

<https://www.phoenixcontact.com/pc/products/0205290>

Test plug strip, number of positions: 1, color: silver-colored



EA 11 - Cover

1024263

<https://www.phoenixcontact.com/pc/products/1024263>

Single cover, for covering one terminal block, snap fit, cannot be labeled, color: transparent



UK 35 - Feed-through terminal block

3008012

<https://www.phoenixcontact.com/pc/products/3008012>



SZS 1,0X6,5 VDE - Screwdriver

1205079

<https://www.phoenixcontact.com/pc/products/1205079>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com