

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 57 A, number of connections: 2, number of positions: 1, connection method: Screw connection, Rated cross section: 10 mm², cross section: 1.5 mm² - 16 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: dark gray

Commercial data

Item number	3246340
Packing unit	50 pc
Minimum order quantity	50 pc
Product key	BEK211
GTIN	4046356608428
Weight per piece (including packing)	15.368 g
Weight per piece (excluding packing)	15.368 g
Customs tariff number	85369010
Country of origin	CN

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



Technical data

Product properties

Product family	TB
Number of positions	1
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.82 W

Connection data

Number of connections per level	2
Nominal cross section	10 mm ²
Rated cross section AWG	6
Connection method	Screw connection
Screw thread	M4
Tightening torque	1.2 ... 1.5 Nm
Stripping length	10 mm
Internal cylindrical gage	A6
	B6
Connection in acc. with standard	IEC 60947-7-1
Conductor cross-section rigid	1.5 mm ² ... 16 mm ²
Cross section AWG	14 ... 6 (converted acc. to IEC)
Conductor cross-section flexible	1.5 mm ² ... 10 mm ²
Conductor cross-section, flexible [AWG]	14 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm ² ... 10 mm ²
Flexible conductor cross-section (ferrule with plastic sleeve)	1.5 mm ² ... 6 mm ²
2 conductors with same cross section, rigid	0.5 mm ² ... 4 mm ²
2 conductors with the same cross-section AWG rigid	20 ... 10 (converted acc. to IEC)
2 conductors with same cross section, flexible	0.5 mm ² ... 4 mm ²
2 conductors with the same cross-section AWG flexible	20 ... 10 (converted acc. to IEC)
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.5 mm ² ... 2.5 mm ²
Nominal cross section	10 mm ²
Nominal current	57 A
Maximum load current	57 A (with 16 mm ² conductor cross-section)
Nominal voltage	800 V

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Dimensions

Width	10.2 mm
End cover width	1.8 mm
Height	42.5 mm
Depth on NS 32	52 mm
Depth on NS 35/7,5	47 mm
Depth on NS 35/15	54.5 mm

Material specifications

Color	traffic gray B (RAL 7043)
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 10 mm ²	1.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	5 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross-section/weight	1.5 mm ² / 0.4 kg
	10 mm ² / 2 kg
	16 mm ² / 2.9 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2022-06
Spectrum	Long life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s ²) ² /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



Drawings

Circuit diagram



TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/il/products/3246340>

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	600 V	65 A	16 - 6	-
C				
	600 V	65 A	16 - 6	-

 EAC Approval ID: KZ7500651131219505				
---	--	--	--	--

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Classifications

ECLASS

ECLASS-13.0	27250101
ECLASS-15.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

EF3.1 Climate Change

CO2e kg	0.168 kg CO2e
---------	---------------

TB 10 I - Feed-through terminal block



3246340

<https://www.phoenixcontact.com/il/products/3246340>

Accessories

i Note: Applying some accessories below might limit this product.

SCBI 10-10 - Fixed bridge

3246146

<https://www.phoenixcontact.com/il/products/3246146>



Fixed bridge, number of positions: 10, color: silver-colored

i Max. current carrying capacity: 57 A

SCBI 10-10 ISO - Isolator bridge bar

3251221

<https://www.phoenixcontact.com/il/products/3251221>



Isolator bridge bar, for switchable cross bridges, with insulating collar, pitch: 10.3 mm, number of positions: 10, length: 22 mm, color: silver-colored

i Max. current carrying capacity: 50 A

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



SCBI 10-10 W - Screw bridge

3000836

<https://www.phoenixcontact.com/il/products/3000836>



Screw bridge, with spring washer and insulating collar, pitch: 10.2 mm, number of positions: 10, color: silver-colored

 Max. current carrying capacity: 57 A

INB 10-10 - Insertion bridge

3246201

<https://www.phoenixcontact.com/il/products/3246201>



Insertion bridge, pitch: 10 mm, number of positions: 10, color: gray

 Max. current carrying capacity: 53 A

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



D-TB 4/10 - Cover

3059809

<https://www.phoenixcontact.com/il/products/3059809>

Cover, depth: 35.9 mm, width: 1.8 mm, height: 42.5 mm, color: dark gray



TS-TB - Insulation plate

3062838

<https://www.phoenixcontact.com/il/products/3062838>

Insulation plate, for electrical isolation of neighboring bridges in the terminal center, depth: 22 mm, height: 22 mm, color: dark gray



TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



ATP-TB - Partition plate

3046272

<https://www.phoenixcontact.com/il/products/3046272>



Partition plate, depth: 45.7 mm, width: 3 mm, height: 56 mm, color: dark gray

UM-TM (10X10) - Marker for terminal blocks

0830914

<https://www.phoenixcontact.com/il/products/0830914>



Marker for terminal blocks, Strip, white, unmarked, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: latching, Number of individual labels: 12, text field height: 10 mm, text field width: 10 mm

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/il/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/il/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver-colored

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/il/products/0311647>

Test plug, number of positions: 1, color: silver



PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/il/products/0311566>

Insulating sleeve, number of positions: 1, color: white



TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/il/products/0311579>

Insulating sleeve, number of positions: 1, color: red



PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/il/products/0311582>

Insulating sleeve, number of positions: 1, color: blue



TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/il/products/0311595>

Insulating sleeve, number of positions: 1, color: yellow



PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/il/products/0311605>

Insulating sleeve, number of positions: 1, color: green



TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/il/products/0311621>



Insulating sleeve, number of positions: 1, color: gray

PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/il/products/0311634>



Insulating sleeve, number of positions: 1, color: black

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>



PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/il/products/0311618>



Insulating sleeve, number of positions: 1, color: violet

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/il/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

TB 10 I - Feed-through terminal block

3246340

<https://www.phoenixcontact.com/il/products/3246340>




E/TB - End bracket

3246966

<https://www.phoenixcontact.com/il/products/3246966>

End bracket, material: PA, mounting type: NS 35/7,5, NS 35/15, color: dark gray



SCBI 10-10 - Fixed bridge

3246146

<https://www.phoenixcontact.com/il/products/3246146>

Fixed bridge, number of positions: 10, color: silver-colored



Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Israel Ltd.
P.O.B. 1799 Industrial Park Hasharon
Quadima 60920
+972-9-8915700
info@phoenixcontact.co.il